


# AGRIMAX RT 657

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>600/65 R 34</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | VENDIMIADORA / TRACTOR / COSECHADORA   |
| <b>VERSIÓN</b>      | SPECIAL  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 157 D ; 160 A8   |



## DIMENSIONES US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CÓDIGO USA</b> | 94062638 | <b>RC (IN)</b> | 195.3          |
| <b>SW (IN)</b>    | 24.1     | <b>RIM REC</b> | DW 20 B        |
| <b>OD (IN)</b>    | 64.7     | <b>RIM ALT</b> | W 18 L         |
| <b>SLR (IN)</b>   | 29.2     | <b>ECE</b>     | E4-106R-001405 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23    | 29    | 35    |
|-----------|------|------|------|------|------|-------|-------|-------|
| 40        | 4360 | 5090 | 5730 | 6370 | 7010 | 7550  | 8370  | 9100  |
| 30        | 4600 | 5360 | 6030 | 6690 | 7360 | 7940  | 8800  | 9560  |
| 25        | 4760 | 5560 | 6250 | 6940 | 7640 | 8230  | 9130  | 9920  |
| 20        | 5030 | 5860 | 6590 | 7330 | 8060 | 8690  | 9630  | 10460 |
| 5 LT      | 5850 | 6830 | 7680 | 8540 | 9390 | 10120 | 11220 | 12190 |
| 5 HT      | 5030 | 5860 | 6590 | 7330 | 8060 | 8690  | 9630  | 10460 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.