


# AGRIMAXFACTOR

<b>TYRE SIZE</b>	<b>420/70 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	134 D ; 137 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94513635	<b>RC (IN)</b>	163.5
<b>SW (IN)</b>	16.9	<b>RIM REC</b>	W 13
<b>OD (IN)</b>	54.8	<b>RIM ALT</b>	W 12; W 14 L
<b>SLR (IN)</b>	24.9	<b>ECE</b>	E11-106R-0010948

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23
40	2580	3000	3420	3840	4250	4670
30	2710	3150	3590	4030	4480	4920
25	2820	3280	3750	4210	4670	5130
15	2970	3450	3940	4420	4910	5380
5 LT	3450	4020	4590	5150	5710	6270
5 HT	2970	3450	3940	4420	4910	5380

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.