DATA SHEET

PRINTED ON
23-04-2026

AS 504

TIRE SIZE	**19.0/45 - 17**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	LEVANTADOR TELESCÓPICO / REBOQUE PARA OS CAMPOS / IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	134 A8
LI/SS FREE ROLLING	147 A8

DIMENSÕES US STANDARD

CÓDIGO USA	94064465	**RC (IN)**	101.5
SW (IN)	18.3	**RIM REC**	16.00
OD (IN)	34.1	**ECE**	E11-106R-006179
SLR (IN)	15.3	**PR**	16

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	45
5 FR	9520
15 FR	8090
20 FR	7615
25 FR	6800
5 DW	6550
15 DW	5570
20 DW	5240
25 DW	4680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..