


# AGRIMAX RT 600

<b>TIRE SIZE</b>	<b>800/65 R 32</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MAȘINĂ DE RECOLTARE / MAȘINĂ DE ÎMPRĂȘTIAT / TRACTOR / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	181 A8 ; 178 B



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	775	<b>RIM REC</b>	DW 27 B
<b>OD (MM)</b>	1820	<b>RIM ALT</b>	DH 27 B; DW 25 B
<b>SLR (MM)</b>	823	<b>ECE</b>	E4-106R-001429
<b>RC (MM)</b>	5558	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	3175	3660	4485	4900	5385	5865	6350	6900	7500	-	-
40	3450	3975	4875	5325	5850	6375	6900	7500	8250	-	-
30	3695	4255	5220	5700	6260	6825	7385	8025	8830	-	-
10 LT	4625	5330	6535	7140	7840	8545	9250	10050	11055	-	-
10 HT	3695	4255	5220	5700	6260	6825	7385	8025	8830	-	-
10 CYC	-	5655	7230	7960	9250	10140	11055	12025	12440	13000	14000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.