

# FLOTATION TR 675

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>550/45 - 22.5</b>   |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       | ❖ BIAS   |
| <b>MACHINERY</b>          | LANDWIRTSCHAFTLICHE GERÄTE / ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE |
| <b>VERSION</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS DRIVE WHEEL</b>  | 154 A8/150 B   |
| <b>LI/SS FREE ROLLING</b> | 166 A8/162 B   |



## ABMESSUNGEN IS STANDARD

|                |                |           |    |
|----------------|----------------|-----------|----|
| <b>SW (MM)</b> | 543            | <b>PR</b> | 20 |
| <b>OD (MM)</b> | 1070           |           |    |
| <b>RIM REC</b> | AG 16.00       |           |    |
| <b>ECE</b>     | E4-106R-002723 |           |    |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.00 | 3.50 | 4.00 |
|------------|------|------|------|
| 10 FR      | 6270 | 6860 | 7420 |
| 20 FR      | 5645 | 6175 | 6680 |
| 30 FR      | 5020 | 5490 | 5935 |
| 40 FR      | 4480 | 4900 | 5300 |
| 50 FR      | 4030 | 4410 | 4750 |
| 10 DW      | 4440 | 4860 | 5250 |
| 20 DW      | 3995 | 4370 | 4725 |
| 30 DW      | 3550 | 3885 | 4200 |
| 40 DW      | 3170 | 3470 | 3750 |
| 50 DW      | 2855 | 3125 | 3350 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.