

AS 504

TIRE SIZE	11.5/80 - 15.3
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	114 A8
LI/SS FREE ROLLING	126 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	290	RIM REC	9.00
OD (MM)	867	ECE	E4-106R-001892
SLR (MM)	380	PR	8
RC (MM)	2540	SRI	410

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.70
10 FR	2380
25 FR	2025
30 FR	1905
40 FR	1700
10 DW	1650
25 DW	1405
30 DW	1320
40 DW	1180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.