


MULTIMAX MP 527

| | |
|---------------------|--|
| TIRE SIZE | 400/70 R 20 IND |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 149 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|--------------------|
| SW (MM) | 404 | RIM REC | 13 |
| OD (MM) | 1068 | RIM ALT | 12 SDC; 13 SDC; 14 |
| SLR (MM) | 494 | ECE | E4-106R-002656 |
| RC (MM) | 3282 | SRI | 525 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.5 | 4.0 | 4.2 | 4.4 |
|------------|------|------|------|------|------|------|------|------|------|
| 50 | 1560 | 1855 | 2115 | 2405 | 2700 | 2895 | 3250 | - | - |
| 40 | 1560 | 1855 | 2115 | 2405 | 2700 | 2895 | 3250 | - | - |
| 30 | 1675 | 1985 | 2265 | 2580 | 2890 | 3100 | 3480 | - | - |
| 25 | 1735 | 2060 | 2350 | 2675 | 3000 | 3215 | 3610 | - | - |
| 10 CYC. | 1905 | 2340 | 2755 | 3170 | 3610 | 3925 | 4440 | 4680 | 4875 |
| STATIC | 2920 | 3590 | 4225 | 4860 | 5535 | 6020 | 6805 | 7180 | 7475 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.