


# EARTHMAX SR 41

<b>TIRE SIZE</b>	<b>875/65 R 29</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	БУЛЬДОЗЕР / ПОГРУЗЧИК / ШАРНИРНО-СОЧЛЕНЕННЫЙ САМОСВАЛ / НИЗКОПРОФИЛЬНЫЙ САМОСВАЛ
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	221 A2



## РАЗМЕРЫ IS STANDARD

<b>OD (MM)</b>	1865	<b>RIM ALT</b>	27.00/3.0; 28.00/3.5
<b>SLR (MM)</b>	837	<b>TRA CODE</b>	L4
<b>RC (MM)</b>	5680	<b>STAR RATING</b>	★★
<b>RIM REC</b>	27.00/3.5		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	5.00	5.25	5.50	5.75	6.00	6.25
10	21800	23000	23600	24300	25000	25750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.