

AS 504

TIRE SIZE	19.0/45 - 17
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	134 A8
LI/SS FREE ROLLING	147 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	465	RIM REC	16.00
OD (MM)	865	ECE	E11-106R-006179
SLR (MM)	389	PR	16
RC (MM)	2578	SRI	410

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.10
10 FR	4305
25 FR	3660
30 FR	3445
40 FR	3075
10 DW	2970
25 DW	2525
30 DW	2375
40 DW	2120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.