

AW 705

| | |
|---------------------------|--|
| TIRE SIZE | 16.0/70 - 20 |
| UM | IS STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | PRESSA PER BALLE DI FIENO / ATTREZZI AGRICOLI / RIMORCHIO / MIETITREBBIA / ATTREZZI AGRICOLI |
| VERSIONE | STANDARD |
| TIRE TYPE | TT |
| LI/SS FREE ROLLING | 154 A8 |



DIMENSIONI IS STANDARD

| | | | |
|-----------------|------|----------------|--------------------|
| SW (MM) | 408 | RIM REC | 13.0 |
| OD (MM) | 1075 | RIM ALT | 12 SDC; 13 SDC; 14 |
| SLR (MM) | 480 | ECE | E11-106R-003368 |
| RC (MM) | 3155 | PR | 14 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.50 |
|-------------------|-------------|
| 10 FR | 5250 |
| 25 FR | 4465 |
| 30 FR | 4200 |
| 40 FR | 3750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.