

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>250/85 R 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZADOR AGRÍCOLA / VINDIMADORA / TRATOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	109 A8/B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94028177	<b>RC (IN)</b>	122.2
<b>SW (IN)</b>	9.9	<b>RIM REC</b>	W 8
<b>OD (IN)</b>	40.8	<b>RIM ALT</b>	W 7; W 9
<b>SLR (IN)</b>	18.7	<b>ECE</b>	E4-106R-000638

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	1260	1450	1660	1860	2070	2270
25	1260	1450	1660	1860	2070	2270
20	1340	1570	1790	2010	2230	2440
5 LT	1690	1960	2240	2510	2790	3050
5 HT	1340	1570	1790	2010	2230	2440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.