

# AT 621

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 15.5/60 - 18   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> | ⊠ BIAS   |
| <b>MACHINERY</b>    | KOMPAKTHJULLASTARE /<br>GRÄVLASTARE / GRÄVLASTARE /<br>HJULLASTARE |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 139 A2   |



## DIMENSIONER US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94028542 | <b>RC (IN)</b> | 113.0           |
| <b>SW (IN)</b>  | 15.5     | <b>RIM REC</b> | W 13            |
| <b>OD (IN)</b>  | 37.0     | <b>ECE</b>     | E11-106R-003575 |
| <b>SLR (IN)</b> | 16.9     | <b>PR</b>      | 10              |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>38</b> |
| 5                | 5360      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.