

AS 504

TIRE SIZE	16.5/85 - 24
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	155 A8
LI/SS FREE ROLLING	168 A8



РАЗМЕРЫ US STANDARD

USA CODE	94019113	RC (IN)	158.0
SW (IN)	16.3	RIM REC	W 13
OD (IN)	52.2	RIM ALT	W 14 L; W 15 L
SLR (IN)	23.0	ECE	E4-106R-001877

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	55
5 FR	17280
15 FR	14690
20 FR	13820
25 FR	12350
5 DW	11960
15 DW	10160
20 DW	9570
25 DW	8540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.