


# RIDEMAX FL 693 M



<b>TIRE SIZE</b>	710/50 R 26.5
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TANKER / TRAILER / IMPLEMENTS
<b>VERSION</b>	HD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	179 D

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	727	<b>RIM REC</b>	AG 24.00
<b>OD (MM)</b>	1383	<b>RIM ALT</b>	AG 20.00
<b>SLR (MM)</b>	606	<b>ECE</b>	E11-106R-006008
<b>RC (MM)</b>	4217	<b>SRI</b>	650

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
70	1765	2260	2825	3175	3670	4165	4590	5010	5505	6210	7055
65	1940	2480	3100	3490	4030	4575	5040	5505	6045	6820	7750
50	2345	3005	3755	4225	4880	5535	6100	6660	7320	8255	9380
40	2635	3375	4220	4745	5485	6220	6855	7485	8225	9280	10540
30	2930	3750	4685	5270	6090	6910	7610	8315	9130	10305	11705
25	3065	3920	4900	5515	6370	7225	7960	8695	9555	10780	12245
10	3490	4465	5580	6280	7255	8235	9070	9905	10885	12280	13950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.