

# POWER TRAX HD (FL)

|                     |             |
|---------------------|-------------|
| <b>TYRE SIZE</b>    | 8.25 - 15   |
| <b>UM</b>           | US STANDARD |
| <b>CONSTRUCTION</b> | ⊗ BIAS      |
| <b>VERSION</b>      | STANDARD    |
| <b>TYRE TYPE</b>    | TT          |



## DIMENSIONS US STANDARD

|                 |          |                |     |
|-----------------|----------|----------------|-----|
| <b>USA CODE</b> | 94026012 | <b>RIM ALT</b> | 7.0 |
| <b>SW (IN)</b>  | 9.8      | <b>PR</b>      | 16  |
| <b>OD (IN)</b>  | 33.3     |                |     |
| <b>RIM REC</b>  | 6.50     |                |     |

## LOAD CAPACITY (LBS/TYRE)

| <b>MPH / PSI</b>          | <b>134</b> |
|---------------------------|------------|
| <b>15 LOAD WHEEL</b>      | 10175      |
| <b>15 STEER WHEEL</b>     | 7825       |
| <b>5 OTHER VEHICLES</b>   | 10175      |
| <b>15 OTHER VEHICLES</b>  | 7825       |
| <b>STATIC SIDE LOADER</b> | 11815      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.