


AGRIMAX V- FLECTO

TIRE SIZE	VF 900/60 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	189 D



DIMENSIONES US STANDARD

CÓDIGO USA	94065257	RC (IN)	251.6
SW (IN)	35.4	RIM REC	DW 30B
OD (IN)	84.3	ECE	E11-106R-006165
SLR (IN)	36.9		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	10120	11770	13620	15280	16930	15890	20660
FROM 40 TO 25	11120	12940	14980	16800	18620	20440	22710
20	11340	13190	15280	17130	18980	20840	23160
12	11560	13450	15570	17460	19360	21250	23610
5	12220	14230	16470	18470	20470	22470	24980
*UPTO 5 CYC WITH FRONT LOADER	15560	18110	20960	23510	26060	28600	31790
5 HT	11340	13190	15280	17130	18980	20840	23160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.