


# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>240/60 R 12</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN FÖR FRUKTODLING / LITEN TRAKTOR / TRAKTOR / SKÖRDEMASKIN
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	89 A8 ; B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94070657	<b>RC (IN)</b>	70.0
<b>SW (IN)</b>	9.5	<b>RIM REC</b>	7
<b>OD (IN)</b>	23.3	<b>ECE</b>	E11-106R-007679
<b>SLR (IN)</b>	10.6		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	600	690	790	880	990	1070	1200	1280
25	600	690	790	880	990	1070	1200	1280
20	640	740	850	940	1050	1150	1290	1380
5 LT	800	920	1060	1180	1320	1440	1610	1720
5 HT	640	740	850	940	1050	1150	1290	1380

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.