DATA SHEET

PRINTED ON
21-04-2026

AS 504

TIRE SIZE	**7.5L - 15**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	SOLLEVATORE TELESCOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESCOPICO
VERSIONE	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	97 A8
LI/SS FREE ROLLING	109 A8

DIMENSIONI US STANDARD

CODICE USA	94019397	**RC (IN)**	89.8
SW (IN)	8.3	**RIM REC**	6 LB
OD (IN)	30.1	**RIM ALT**	5 K; 5½ J; 5½ K
SLR (IN)	13.9	**ECE**	E11-106R-004238

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	45
5 FR	3170
15 FR	2700
20 FR	2550
25 FR	2270
5 DW	2250
15 DW	1920
20 DW	1810
25 DW	1610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..