

# FLOTATION 648

<b>TIRE SIZE</b>	<b>500/50 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊗ BIAS
<b>MACHINERY</b>	BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	151 A8/147 B
<b>LI/SS FREE ROLLING</b>	163 A8/159 B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94037827	<b>RC (IN)</b>	126.0
<b>SW (IN)</b>	19.7	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	42.1	<b>ECE</b>	E11-106R-003400
<b>SLR (IN)</b>	18.7	<b>PR</b>	20

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	49	52	55
5 FR	14110	14580	15050
10 FR	12700	13130	13550
20 FR	11290	11660	12040
25 FR	10070	10420	10750
30 FR	9070	9380	9640
5 DW	9990	10330	10650
10 DW	8980	9290	9580
20 DW	7990	8260	8520
25 DW	7130	7370	7610
30 DW	6420	6640	6780

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.