


MULTIMAX MP 522

TIRE SIZE	440/80 R 24 IND
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	KOMPAKTLADER / TELESKOPLADER / KOMPAKTLADER / TELESKOPLADER
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	161 A8/B



ABMESSUNGEN IS STANDARD

SW (MM)	441	RIM REC	DW 14 L
OD (MM)	1314	RIM ALT	DW 13 ; DW 13 L ; DW 15 L
SLR (MM)	586	ECE	E11-106R-002966
RC (MM)	3958	SRI	625

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	2220	2640	3010	3425	3840	4120	4625	-	-
40	2220	2640	3010	3425	3840	4120	4625	-	-
30	2380	2825	3220	3665	4110	4410	4950	-	-
25	2465	2930	3340	3800	4265	4575	5135	-	-
10 CYC.	2710	3335	3925	4515	5140	5590	6320	6665	6940
STATIC	4150	5110	6015	6920	7875	8570	9685	10215	10640

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.