


# FL 630 SUPER

|                     |  |
|---------------------|--|
|                     | <b>750/60 R 26.5</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | YAYICI / TANKER / RÖMORK / UYGULAMALI MAKINE   |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
|                     | 180 D  |



## UNDEFINED US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94042135 | <b>RC (IN)</b> | 189.0          |
| <b>SW (IN)</b>  | 29.7     | <b>RIM REC</b> | AG 24.00       |
| <b>OD (IN)</b>  | 62.0     | <b>ECE</b>     | E4-106R-001427 |
| <b>SLR (IN)</b> | 27.3     |                |                |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12    | 15    | 17    | 23    | 29    | 35    | 41    | 46    | 52    | 58    |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45        | 5160  | 5960  | 6770  | 8210  | 9500  | 10950 | 12400 | 13360 | 14810 | 16090 |
| 40        | 5640  | 6530  | 7410  | 8990  | 10410 | 11990 | 13580 | 14640 | 16230 | 17640 |
| 30        | 6830  | 7900  | 8970  | 10890 | 12600 | 14520 | 16430 | 17710 | 19640 | 21340 |
| 25        | 7680  | 8880  | 10070 | 12230 | 14150 | 16310 | 18470 | 19920 | 22070 | 23980 |
| 15        | 8920  | 10320 | 11710 | 14220 | 16450 | 18960 | 21460 | 23140 | 25640 | 27860 |
| 5         | 10160 | 11750 | 13340 | 16190 | 18740 | 21590 | 24450 | 26350 | 29210 | 31740 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.