

# TR 126

|                     |                       |
|---------------------|-----------------------|
| <b>TIRE SIZE</b>    | 7 - 14                |
| <b>UM</b>           | IS STANDARD           |
| <b>CONSTRUCTION</b> | BIAS                  |
| <b>MACHINERY</b>    | TRACTOR MIC / TRACTOR |
| <b>VERSION</b>      | STANDARD              |
| <b>TIRE TYPE</b>    | TT                    |
| <b>LI/SS</b>        | 95 A6                 |



## DIMENSIUNI IS STANDARD

|                 |      |                 |                 |
|-----------------|------|-----------------|-----------------|
| <b>SW (MM)</b>  | 170  | <b>RIM REC</b>  | 5 JA; 5 KB      |
| <b>OD (MM)</b>  | 690  | <b>ECE</b>      | E11-106R-005233 |
| <b>SLR (MM)</b> | 320  | <b>PR</b>       | 8               |
| <b>RC (MM)</b>  | 2070 | <b>TRA CODE</b> | R1              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.00</b> |
| 30                | 690         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.