


AGRIMAX RT 657

TIRE SIZE	440/65 R 24
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	VINDIMADORA / TRATOR / CEIFEIRA
VERSÃO	SPECIAL
TIRE TYPE	TL
LI/SS	135 D ; 138 A8



DIMENSÕES IS STANDARD

SW (MM)	441	RIM REC	W 14 L
OD (MM)	1182	RIM ALT	W 13 ; W 15 L
SLR (MM)	538	ECE	E4-106R-000616
RC (MM)	3546	SRI	575

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1050	1225	1375	1530	1680	1810	2010	2180
50	1100	1285	1445	1605	1765	1905	2110	2290
40	1135	1325	1490	1655	1820	1960	2175	2360
30	1205	1410	1585	1760	1935	2085	2310	2510
10 LT	1405	1640	1845	2050	2255	2430	2695	2925
10 HT	1205	1410	1585	1760	1935	2085	2310	2510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.