


AGRIMAX RT 765

TIRE SIZE	280/70 R 20
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	116 A8/B



РАЗМЕРЫ US STANDARD

USA CODE	94044238	RC (IN)	106.5
SW (IN)	10.8	RIM REC	W 9
OD (IN)	35.4	RIM ALT	W 8; W 10
SLR (IN)	16.1	ECE	E4-106R-00641

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	1300	1490	1710	1930	2150	2370	2570	2760
25	1300	1490	1710	1930	2150	2370	2570	2760
20	1390	1600	1840	2070	2310	2550	2760	2950
5 LT	1740	2000	2290	2590	2890	3190	3440	3690
5 HT	1390	1600	1840	2070	2310	2550	2760	2950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.