

AGRIMAX RT 855

TIRE SIZE	420/85 R 34
UM	IS STANDARD
MACHINERY	PULVÉRISATEUR / MACHINE À VENDANGER / TRACTEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	147 A8/B



DIMENSIONS IS STANDARD

SW (MM)	438	ECE	E11-106R-005179
OD (MM)	1578	SRI	750
SLR (MM)	728	TRA CODE	R1W
RC (MM)	4782	TREAD DEPTH (MM)	48,5
RIM REC	W 15 L	TKPH (TK/H)	0
RIM ALT	W 13 ; W 14 L		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	1450	1665	1910	2155	2400	2645	2895	3075
40	1450	1665	1910	2155	2400	2645	2895	3075
30	1550	1780	2045	2310	2575	2835	3100	3295
10 LT	1940	2230	2560	2890	3220	3550	3880	4125
10 HT	1550	1780	2045	2310	2575	2835	3100	3595

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.