

# FLOTATION 648

	<b>600/55 - 26.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	BALYA MAKINESI / BIÇERDÖVER / YAYICI / BIÇERDÖVER / UYGULAMALI MAKINE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	160 A8/157 B
	172 A6/169 B



## UNDEFINED US STANDARD

<b>USA CODE</b>	94030972	<b>RC (IN)</b>	158.1
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	53.3	<b>ECE</b>	E11-106R-004556
<b>SLR (IN)</b>	22.9	<b>PR</b>	18

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	39	41	42
5 FR	18640	19050	19440
10 FR	16780	17140	17500
20 FR	14910	15230	15550
25 FR	13320	13600	13890
30 FR	11980	12250	12790
5 DW	13320	13610	13890
10 DW	11980	12250	12500
20 DW	10660	10890	11110
25 DW	9510	9720	9920
30 DW	8560	8750	9090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.