

# AT 625

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>16.9 - 28</b>                               |
| <b>UM</b>           | IS STANDARD                                    |
| <b>CONSTRUCTION</b> | ⊠ BIAS   |
| <b>MACHINERY</b>    | HARVESTER / BACKHOE LOADER /<br>COMPACT LOADER |
| <b>VERSION</b>      | SPECIAL  |
| <b>TIRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 152 A8   |



## DIMENSIONS IS STANDARD

|                 |      |                 |         |
|-----------------|------|-----------------|---------|
| <b>SW (MM)</b>  | 450  | <b>RIM REC</b>  | DW 15 L |
| <b>OD (MM)</b>  | 1415 | <b>RIM ALT</b>  | DW 14 L |
| <b>SLR (MM)</b> | 645  | <b>PR</b>       | 12      |
| <b>RC (MM)</b>  | 4254 | <b>TRA CODE</b> | R4      |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.60</b> |
| 40                | 3550        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.