

# TR 135

|                     |                      |
|---------------------|----------------------|
| <b>TIRE SIZE</b>    | <b>13.6 - 38</b>     |
| <b>UM</b>           | IS STANDARD          |
| <b>CONSTRUCTION</b> | ⊠ BIAS               |
| <b>MACHINERY</b>    | TRATTORE / RIMORCHIO |
| <b>VERSIONE</b>     | STANDARD             |
| <b>TIRE TYPE</b>    | TT                   |
| <b>LI/SS</b>        | 131 A6               |



## DIMENSIONI IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 345  | <b>RIM REC</b> | W 12           |
| <b>OD (MM)</b>  | 1565 | <b>RIM ALT</b> | W 11           |
| <b>SLR (MM)</b> | 735  | <b>ECE</b>     | E4-106R-002039 |
| <b>RC (MM)</b>  | 4832 | <b>PR</b>      | 8              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.00</b> |
| 30                | 1950        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.