


AGRIMAX FORCE

| | |
|---------------------|--|
| TIRE SIZE | IF 900/60 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HARVESTER / HIGH-POWER TRACTOR / TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 184 D |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 916 | RIM REC | DW 30 A; DW 30 B |
| OD (MM) | 2045 | RIM ALT | TW 31 B |
| SLR (MM) | 904 | ECE | E11-106R-006493 |
| RC (MM) | 6107 | SRI | 975 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|----------------------|------|------|------|-------|-------|-------|-------|-------|
| 70 | 3765 | 4340 | 4995 | 5565 | 6220 | 6795 | 7615 | 8190 |
| FROM 65 TO 40 | 4140 | 4770 | 5490 | 6120 | 6840 | 7470 | 8370 | 9000 |
| 30 | 4305 | 4960 | 5705 | 6360 | 7110 | 7765 | 8700 | 9360 |
| 20 | 4470 | 5150 | 5925 | 6605 | 7385 | 8065 | 9035 | 9720 |
| 10 | 5255 | 6055 | 6970 | 7770 | 8685 | 9485 | 10625 | 11430 |
| UPTO 30 CYC | 5380 | 6200 | 7135 | 7955 | 8890 | 9710 | 10880 | 11700 |
| UPTO 15 CYC | 6415 | 7390 | 8505 | 9485 | 10600 | 11575 | 12970 | 13950 |
| UPTO 10 CYC | 7035 | 8105 | 9330 | 10400 | 11625 | 12695 | 14225 | 15300 |
| 10 HT | 4305 | 4960 | 5705 | 6360 | 7110 | 7765 | 8700 | 9360 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.