


# AGRIMAX FORCE

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>IF 650/75 R 38</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | MAȘINĂ DE RECOLTARE / TRACTOR DE MARE PUTERE / TRACTOR                                   |
| <b>VERSION</b>      | SPECIAL  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 175 D  |



## DIMENSIUNI IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 651  | <b>RIM REC</b> | DW 23 B         |
| <b>OD (MM)</b>  | 1941 | <b>RIM ALT</b> | DW 21 B         |
| <b>SLR (MM)</b> | 866  | <b>ECE</b>     | E11-106R-007385 |
| <b>RC (MM)</b>  | 5802 | <b>SRI</b>     | 925             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR           | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6   | 2.0   | 2.4   |
|----------------------|------|------|------|------|------|-------|-------|-------|
| 70                   | 2955 | 3395 | 3895 | 4400 | 4900 | 5405  | 5905  | 6280  |
| <b>FROM 65 TO 40</b> | 3245 | 3730 | 4280 | 4830 | 5385 | 5935  | 6490  | 6900  |
| 30                   | 3375 | 3880 | 4455 | 5030 | 5605 | 6175  | 6750  | 7180  |
| 20                   | 3505 | 4030 | 4625 | 5220 | 5815 | 6415  | 7010  | 7455  |
| 10                   | 4120 | 4735 | 5435 | 6140 | 6840 | 7540  | 8240  | 8765  |
| <b>UPTO 30 CYC</b>   | 4220 | 4845 | 5565 | 6280 | 7000 | 7715  | 8435  | 8970  |
| <b>UPTO 15 CYC</b>   | 5030 | 5780 | 6635 | 7490 | 8345 | 9200  | 10055 | 10695 |
| <b>UPTO 10 CYC</b>   | 5515 | 6335 | 7275 | 8215 | 9150 | 10090 | 11030 | 11730 |
| 10 HT                | 3375 | 3880 | 4455 | 5030 | 5605 | 6175  | 6750  | 7180  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.