


AGRIMAX ELOS

| | |
|---------------------|--|
| TIRE SIZE | 480/80 R 42 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 151 A8/B |



ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| USA-CODE | 94040827 | RC (IN) | 221.6 |
| SW (IN) | 19.3 | RIM REC | DW 16 L |
| OD (IN) | 74.4 | RIM ALT | DD 16 L ; W 16 L |
| SLR (IN) | 33.7 | ECE | E4-106R-001481 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-------------|------|------|------|------|------|-------|
| 30 | 4190 | 4870 | 5560 | 6240 | 6920 | 7600 |
| 25 | 4190 | 4870 | 5560 | 6240 | 6920 | 7600 |
| 20 | 4490 | 5210 | 5950 | 6680 | 7420 | 8150 |
| 5 LT | 5610 | 6530 | 7450 | 8370 | 9280 | 10200 |
| 5 HT | 4490 | 5210 | 5950 | 6680 | 7420 | 8150 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.