


AGRIMAX RT 657

| | |
|---------------------|--|
| TIRE SIZE | 420/65 R 30 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | VINDIMADORA / TRATOR / CEIFEIRA |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 136 D ; 139 A8 |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 418 | RIM REC | W 13 |
| OD (MM) | 1308 | RIM ALT | W 12 ; W 11 |
| SLR (MM) | 606 | ECE | E11-106R-002975 |
| RC (MM) | 3952 | SRI | 625 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|------|------|------|------|------|------|------|------|
| 65 | 1055 | 1210 | 1390 | 1570 | 1750 | 1930 | 2085 | 2240 |
| 50 | 1110 | 1275 | 1465 | 1650 | 1840 | 2030 | 2195 | 2355 |
| 40 | 1145 | 1315 | 1510 | 1705 | 1900 | 2090 | 2260 | 2430 |
| 30 | 1215 | 1395 | 1600 | 1810 | 2015 | 2220 | 2400 | 2580 |
| 10 LT | 1415 | 1625 | 1865 | 2105 | 2345 | 2585 | 2795 | 3005 |
| 10 HT | 1215 | 1395 | 1600 | 1810 | 2015 | 2220 | 2400 | 2580 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.