


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>520/85 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	167 A8/B



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	516	<b>RIM REC</b>	DW 16 L ; W 16 A ; DD 16
<b>OD (MM)</b>	1951	<b>RIM ALT</b>	DW 18 A ; DD 18 ; W 18 A ; DD 18 L
<b>SLR (MM)</b>	858	<b>ECE</b>	E4-106R-001491
<b>RC (MM)</b>	5782	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.4	2.8	3.2
<b>50</b>	2270	2640	3015	3385	3755	4125	4635	5070	5450
<b>40</b>	2270	2640	3015	3385	3755	4125	4635	5070	5450
<b>30</b>	2430	2830	3225	3625	4020	4415	4960	5425	5830
<b>10 LT</b>	3045	3540	4040	4535	5035	5530	6210	6795	7305
<b>10 HT</b>	2430	2830	3225	3625	4020	4415	4960	5425	5830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.