


AGRIMAX RT 657

| | |
|---------------------|--|
| | 540/65 R 24 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ÜZÜM HASAT MAKINESİ / TRAKTÖR / BIÇERDÖVER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 146 D ; 149 A8 |



UNDEFINED IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 530 | RIM REC | W 16 L |
| OD (MM) | 1312 | RIM ALT | W 18 L |
| SLR (MM) | 596 | ECE | E4-106R-000773 |
| RC (MM) | 3942 | SRI | 625 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|------|------|------|------|------|------|------|------|
| 65 | 1440 | 1680 | 1890 | 2100 | 2310 | 2490 | 2760 | 3000 |
| 50 | 1515 | 1765 | 1985 | 2205 | 2430 | 2615 | 2900 | 3150 |
| 40 | 1560 | 1820 | 2050 | 2275 | 2505 | 2700 | 2990 | 3250 |
| 30 | 1660 | 1935 | 2175 | 2415 | 2660 | 2865 | 3175 | 3450 |
| 10 LT | 1930 | 2255 | 2535 | 2815 | 3100 | 3340 | 3700 | 4020 |
| 10 HT | 1660 | 1935 | 2175 | 2415 | 2660 | 2865 | 3175 | 3450 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.