


# AGRIMAX TERIS

|                     |  |
|---------------------|--|
|                     | <b>1050/50 R 32 CHO</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | BIÇERDÖVER / PAMUK TOPLAMA<br>MAKINESİ   |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
|                     | 184 A8 ; 181 B   |



## UNDEFINED US STANDARD

|                 |          |                |                       |
|-----------------|----------|----------------|-----------------------|
| <b>USA CODE</b> | 94032723 | <b>RC (IN)</b> | 223.8                 |
| <b>SW (IN)</b>  | 41.7     | <b>RIM REC</b> | 36.0 VA (multi-piece) |
| <b>OD (IN)</b>  | 74.5     | <b>ECE</b>     | E4-106R-000813        |
| <b>SLR (IN)</b> | 33.1     |                |                       |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12    | 15    | 20    | 23    | 29    | 35    | 41    | 46    |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 8190  | 9280  | 11640 | 12920 | 14370 | 15460 | 16920 | 18190 |
| 25        | 8930  | 10120 | 12700 | 14090 | 15670 | 16860 | 18450 | 19840 |
| 20        | 9560  | 10840 | 13590 | 15080 | 16780 | 18050 | 19750 | 21230 |
| 10 CYC    | 14740 | 16700 | 20950 | 23250 | 25870 | 27830 | 30460 | 32740 |
| 5 CYC     | 16070 | 18220 | 22860 | 25360 | 28220 | 30360 | 33220 | 35710 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.