


# AGRIMAX SPARGO

<b>TIRE SIZE</b>	<b>VF 380/105 R 50</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	179 D



## DIMENSIONI US STANDARD

<b>USA CODE</b>	94048113	<b>RC (IN)</b>	244.5
<b>SW (IN)</b>	15.7	<b>RIM REC</b>	W 13 A
<b>OD (IN)</b>	80.7	<b>RIM ALT</b>	W 12; DW 12; DW 13; DW 13 L
<b>SLR (IN)</b>	36.8	<b>ECE</b>	E4-106R-002397

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	20	23	26	29	32	35	38	41	44	47	49	52	55	58	61	64
45	7460	8390	9160	9640	10100	10410	10720	11350	11810	12270	12750	13210	13520	13990	14300	14920	15550
FROM 40 TO 25	8210	9230	10080	10600	11100	11450	11790	12470	12990	13500	14010	14520	14860	15380	15720	16410	17090
20	8360	9410	10280	10810	11330	11680	12020	12720	13240	13760	14290	14810	15160	15680	16030	16730	17430
12	8530	9590	10490	11020	11550	11910	12260	12970	13510	14040	14570	15110	15460	15990	16350	17060	17770
5	9020	10150	11080	11660	12220	12590	12970	13720	14280	14840	15410	15980	16350	16910	17290	18040	18800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.