


# AGRIMAX V-FLECTO

<b>TIRE SIZE</b>	<b>VF 650/85 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOTORSTARK TRAKTOR / TRAKTOR
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	183 D



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	680	<b>RIM REC</b>	DW 23 B
<b>OD (MM)</b>	2160	<b>RIM ALT</b>	DW20B;DW21B
<b>SLR (MM)</b>	938	<b>ECE</b>	E11-106R-0011307
<b>RC (MM)</b>	6413	<b>SRI</b>	1025

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	3980	4615	5250	5970	6605	7240	7960
<b>FROM 65 TO 40</b>	4375	5075	5775	6560	7260	7960	8750
30	4460	5175	5890	6690	7405	8120	8925
20	4550	5275	6005	6825	7550	8280	9100
10	4810	5580	6350	7215	7985	8755	9625
<b>UPTO 30 CYC</b>	4965	5755	6550	7445	8240	9035	9930
<b>UPTO 15 CYC</b>	5925	6875	7820	8890	9835	10785	11855
<b>UPTO 10 CYC</b>	6495	7530	8570	9740	10780	11820	12990
10HT	4460	5175	5890	6690	7405	8120	8925

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.