

# ROCK GRIP L4

|                     |                       |
|---------------------|-----------------------|
| <b>TIRE SIZE</b>    | 14.00 - 25            |
| <b>UM</b>           | US STANDARD           |
| <b>CONSTRUCTION</b> | ⊠ BIAS                |
| <b>MACHINERY</b>    | ÎNCĂRCĂTOR / BULDOZER |
| <b>VERSION</b>      | STANDARD              |
| <b>TIRE TYPE</b>    | TL                    |



## DIMENSIUNI US STANDARD

|                 |          |                 |           |
|-----------------|----------|-----------------|-----------|
| <b>USA CODE</b> | 94031153 | <b>RIM REC</b>  | 10.00/1.5 |
| <b>OD (IN)</b>  | 55.5     | <b>PR</b>       | 28        |
| <b>SLR (IN)</b> | 25.6     | <b>TRA CODE</b> | L4        |
| <b>RC (IN)</b>  | 164.3    |                 |           |

## LOAD CAPACITY (LBS/TIRE)

|                  |            |
|------------------|------------|
| <b>MPH / PSI</b> | <b>134</b> |
| 5                | 22000      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.