



PRINTED ON  
22-04-2026

## DATA SHEET

# IT 400

|                     |                      |
|---------------------|----------------------|
| <b>TIRE SIZE</b>    | <b>8.25 - 15</b>     |
| <b>UM</b>           | US STANDARD          |
| <b>CONSTRUCTION</b> |                      |
| <b>MACHINERY</b>    | LOW PLATFORM TRAILER |
| <b>VERSION</b>      | STANDARD             |
| <b>TIRE TYPE</b>    | TT                   |
| <b>LI/SS</b>        | 131/126 J            |



### DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94029020 | <b>RC (IN)</b> | 98.9            |
| <b>SW (IN)</b>  | 9.4      | <b>RIM REC</b> | 6.50            |
| <b>OD (IN)</b>  | 33.3     | <b>RIM ALT</b> | 6.0 ; 7.0       |
| <b>SLR (IN)</b> | 14.8     | <b>ECE</b>     | E11-54R-0019536 |

### LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 140  | 130  | 120  |
|-----------|------|------|------|
| 10        | 6945 | -    | -    |
| 20        | -    | 5730 | -    |
| 62 LS     | -    | 4300 | -    |
| 62 LD     | -    | -    | 3750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.