

AGRIMAX FORCE

TIRE SIZE	IF 900/60 R 42 CFO
UM	US STANDARD
MACHINERY	MOISSONNEUSE / TRACTEUR DE FORTE PUISSANCE / TRACTEUR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	186 D



DIMENSIONS US STANDARD

CODE USA	94022236	RC (IN)	252.6
SW (IN)	36.1	RIM REC	DW 30 B
OD (IN)	84.5	RIM ALT	TW 30 B
SLR (IN)	37.4	ECE	E11-106R-006494

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	8760	10100	11620	12950	14480	15820	17710	19060
FROM 40 TO 25	9630	11100	12780	14240	15920	17380	19480	20900
20	10010	11540	13280	14800	16540	18080	20250	21780
12	10390	11980	13790	15380	17180	18770	21030	22620
5	12220	14090	16210	18080	20200	22070	24730	26600
UPTO 20 CYC	12520	14430	16600	18510	20690	22600	25320	27230
UPTO 10 CYC	14920	17200	19800	22070	24670	26940	30180	32460
UPTO 5 CYC	16370	18860	21710	24210	27050	29540	33100	35600
5HT	10010	11540	13280	14800	16540	18080	20250	21780

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.