


# EARTHMAX SR 30

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 20.5 R 25  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | STEL DUMPER / BULLDOZER  |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 177 B ; 186 A2   |



## DIMENSIONER US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>USA CODE</b> | 94027729 | <b>RIM REC</b>     | 17.00/2.0 |
| <b>OD (IN)</b>  | 58.5     | <b>RIM ALT</b>     | 17.00/1.7 |
| <b>SLR (IN)</b> | 26.1     | <b>TRA CODE</b>    | E3/L3     |
| <b>RC (IN)</b>  | 174.8    | <b>STAR RATING</b> | ★★★       |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 58    | 62    | 65    | 69    | 73    | 76    |
|-----------|-------|-------|-------|-------|-------|-------|
| 30        | 12800 | 13600 | 14300 | 14800 | 15200 | 16100 |
| 5         | 17600 | 18200 | 19300 | 19800 | 20900 | -     |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.