


# AGRIMAX RT 855

|                     |  |
|---------------------|--|
|                     | <b>520/85 R 46</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | ILAÇLAMA / ÜZÜM HASAT MAKİNESİ /<br>TRAKTÖR / BIÇERDÖVER /<br>UYGULAMALI MAKİNE          |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
|                     | 173 A8/B   |



## UNDEFINED IS STANDARD

|                 |      |                |                                   |
|-----------------|------|----------------|-----------------------------------|
| <b>SW (MM)</b>  | 516  | <b>RIM REC</b> | DW 16 L ; W 16 A ; W 16 L ; DD 16 |
| <b>OD (MM)</b>  | 2075 | <b>RIM ALT</b> | DW 18 L ; W 18 L ; W 18 A         |
| <b>SLR (MM)</b> | 964  | <b>ECE</b>     | E4-106R-001494                    |
| <b>RC (MM)</b>  | 6310 | <b>SRI</b>     | 975                               |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  |
|------------|------|------|------|------|------|------|------|------|------|------|------|
| 50         | 2340 | 2720 | 3105 | 3485 | 3870 | 4250 | 4875 | 5330 | 5785 | 6175 | 6500 |
| 40         | 2340 | 2720 | 3105 | 3485 | 3870 | 4250 | 4875 | 5330 | 5785 | 6175 | 6500 |
| 30         | 2505 | 2915 | 3325 | 3735 | 4145 | 4550 | 5215 | 5705 | 6190 | 6605 | 6955 |
| 10 LT      | 3135 | 3645 | 4160 | 4670 | 5185 | 5695 | 6535 | 7140 | 7750 | 8275 | 8710 |
| 10 HT      | 2505 | 2915 | 3325 | 3735 | 4145 | 4550 | 5215 | 5705 | 6190 | 6605 | 6955 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.