

AGRIMAX FORTIS

| | |
|---------------------|--------------------|
| TIRE SIZE | 650/85 R 38 |
| UM | US STANDARD |
| CONSTRUCTION | |
| MACHINERY | TRACTOR |
| VERSION | SPECIAL |
| TL/TT | TL |
| LI/SS | 173 D ; 176 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-------------------|
| USA CODE | 94058907 | RC (IN) | 243.5 |
| SW (IN) | 26.6 | RIM REC | DW 23 B |
| OD (IN) | 81.5 | RIM ALT | DW 21 B ; DW 20 B |
| SLR (IN) | 36.8 | ECE | E4-106R-001426 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|
| 40 | 6880 | 8020 | 9030 | 10030 | 11030 | 11890 | 13180 | 14300 |
| 30 | 7230 | 8430 | 9480 | 10540 | 11600 | 12490 | 13840 | 15050 |
| 25 | 7520 | 8770 | 9870 | 10960 | 12060 | 13000 | 14410 | 15650 |
| 20 | 7910 | 9240 | 10380 | 11540 | 12700 | 13680 | 15170 | 16480 |
| 5 LT | 9230 | 10760 | 12100 | 13450 | 14790 | 15940 | 17670 | 19200 |
| 5 HT | 7910 | 9240 | 10380 | 11540 | 12700 | 13680 | 15170 | 16480 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.