


EARTHMAX SR 22



| | |
|---------------------|--|
| | 23.5 R 25 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | GREYDER / YÜKLEYICI / DOZER / YÜKLEYICI / DOZER / GREYDER |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| | 170 A8 ; 195 A2 |

UNDEFINED US STANDARD

| | | | |
|-----------------|----------|--------------------|-----------|
| USA CODE | 94062911 | RIM REC | 19.50/2.5 |
| OD (IN) | 63.5 | TRA CODE | G2/L2 |
| SLR (IN) | 27.9 | STAR RATING | ★ |
| RC (IN) | 191.5 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 18 | 22 | 25 | 29 | 33 | 36 | 40 | 44 | 58 | 62 | 65 | 69 | 73 |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 25 | 6950 | 7850 | 8800 | 9900 | 10700 | 11700 | 12300 | 13200 | - | - | - | - | - |
| 5 | - | - | - | - | - | - | - | - | 22700 | 23400 | 24700 | 25400 | 26800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.