


# AGRIMAX V-FLECTO

<b>TIRE SIZE</b>	<b>VF 650/85 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE A ELEVATA POTENZA / TRATTORE
<b>VERSIONE</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	182 D



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94513543	<b>RC (IN)</b>	240.9
<b>SW (IN)</b>	26.4	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	81.5	<b>RIM ALT</b>	DW 20 B; DW 21 B
<b>SLR (IN)</b>	34.9	<b>ECE</b>	E11-106R-0010579

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	8520	9890	11250	12790	14150	15510	17050
<b>FROM 40 TO 25</b>	9370	10870	12370	14050	15550	17050	18740
20	9560	11080	12610	14330	15860	17380	19110
12	9740	11300	12850	14620	16170	17720	19490
5	10310	11950	13600	15450	17110	18750	20610
<b>UPTO 20 CYC</b>	10630	12320	14030	15940	17650	19340	21260
<b>UPTO 10 CYC</b>	12690	14720	16740	19040	21060	23090	25380
<b>UPTO 5CYC</b>	13910	16130	18350	20870	23080	25310	27820
5 HT	9560	11080	12610	14330	15860	17380	19110

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.