

# AGRIMAX RT 657

**420/65 R 28****UM** IS STANDARD**CONSTRUCTION**  RADIAL**MACHINERY** ÜZÜM HASAT MAKINESİ / TRAKTÖR /  
BIÇERDÖVER**VERSION** STANDARD**TIRE TYPE** TL

135 D ; 138 A8



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	418	<b>RIM REC</b>	W 13
<b>OD (MM)</b>	1257	<b>RIM ALT</b>	W 12; W 11
<b>SLR (MM)</b>	584	<b>ECE</b>	E11-106R-002974
<b>RC (MM)</b>	3824	<b>SRI</b>	600

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>65</b>	1025	1180	1355	1530	1705	1875	2030	2180
<b>50</b>	1080	1240	1420	1605	1790	1970	2130	2290
<b>40</b>	1110	1275	1465	1655	1845	2030	2195	2360
<b>30</b>	1180	1360	1560	1760	1960	2160	2335	2510
<b>10 LT</b>	1375	1580	1815	2050	2285	2520	2725	2925
<b>10 HT</b>	1180	1360	1560	1760	1960	2160	2335	2510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.