DATA SHEET

PRINTED ON
23-04-2026

FLOTATION 648

TIRE SIZE	**600/50 - 22.5**
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	153 A8/149 B
LI/SS FREE ROLLING	165 A8/161 B

DIMENSIONES IS STANDARD

SW (MM)	611	**RIM REC**	AG 20.00
OD (MM)	1170	**ECE**	E4-106R-002306
SLR (MM)	510	**PR**	16
RC (MM)	3501		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.20	2.40	2.60
10 FR	6540	6880	7210
20 FR	5885	6195	6490
30 FR	5230	5505	5770
40 FR	4670	4915	5150
50 FR	4205	4425	4625
10 DW	4635	4880	5110
20 DW	4170	4390	4600
30 DW	3705	3905	4090
40 DW	3310	3485	3650
50 DW	2980	3135	3250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..