

AGRIMAX PROHARVEST

TIRE SIZE	VF 1020/55 R 38
UM	US STANDARD
CONSTRUCTION	
MACHINERY	HARVESTER
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	200 D



DIMENSIONS US STANDARD

USA CODE	94515097	RIM REC	36.00 VA (multi-piece)
SW (IN)	39.8	ECE	E11-106R-0011309
OD (IN)	81.1		
RC (IN)	2.2		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46
45	10960	12640	14330	16290	17980	19950	22190	22470	26120	28090
FROM 40 TO 25	12040	13890	15740	17900	19750	21910	24380	24690	28700	30860
20	12280	14170	16060	18260	20150	22350	24880	25190	29290	31480
12	12520	14450	16380	18620	20550	22790	25360	25680	29860	32100
5	13250	15280	17320	19700	21740	24110	26830	27160	31580	33950
*UPTO 20 CYC	13670	15770	17870	20330	22420	24880	27680	28030	32580	35030
*UPTO 10 CYC	16310	18830	21330	24260	26770	29690	33050	33460	38900	41820
*UPTO 5 CYC	17880	20630	23380	26590	29340	32550	36210	36670	42620	45830
10HT	12280	14170	16060	18260	20150	22350	24880	25190	29290	31480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.