


# AGRIMAX PROCROP

<b>TIRE SIZE</b>	<b>VF 270/95 R 36</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	150 D



## DIMENSIONI US STANDARD

<b>USA CODE</b>	94511570	<b>RC (IN)</b>	173.0
<b>SW (IN)</b>	11.0	<b>RIM REC</b>	W9
<b>OD (IN)</b>	56.7	<b>ECE</b>	E11-106R-0010172
<b>SLR (IN)</b>	26.2		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	14	17	20	23	29	35	41	46	52	58
45	3170	3580	3970	4310	4790	5050	5530	5990	6400	6730
FROM 40 TO 25	3480	3930	4370	4730	5250	5550	6070	6590	7030	7390
20	3550	4010	4460	4830	5360	5660	6190	6720	7170	7540
12	3620	4080	4550	4930	5460	5770	6310	6850	7310	7690
5	3830	4310	4800	5210	5780	6100	6670	7240	7730	8130

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.