

# AW 702

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>10.50 - 16</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> | ⊠ BIAS   |
| <b>MACHINERY</b>    | ENFARDADEIRA DE FENO /<br>IMPLEMENTOS AGRÍCOLAS /<br>REBOQUE / CEIFEIRA / IMPLEMENTOS<br>AGRÍCOLAS / REBOQUE |
| <b>VERSÃO</b>       | STANDARD   |
| <b>TIRE TYPE</b>    | TT   |



## DIMENSÕES US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CÓDIGO USA</b> | 94009893 | <b>RC (IN)</b> | 117.6           |
| <b>SW (IN)</b>    | 12.0     | <b>RIM REC</b> | 6.00 T          |
| <b>OD (IN)</b>    | 38.4     | <b>ECE</b>     | E11-106R-004244 |
| <b>SLR (IN)</b>   | 17.5     | <b>PR</b>      | 14              |

## LOAD CAPACITY (LBS/TIRE)

|                  |            |
|------------------|------------|
| <b>MPH / PSI</b> | <b>100</b> |
| 30               | 7090       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.